

Technische Daten

Typ	EU10L	EU13L	EU15L	EU20L	EU35L
Höhe x Breite x Tiefe (mm)	1750 x 960 x 610			1772 x 1160 x 800	2320 x 1700 x 1190
Nennleistung (-10°C)	9,2 kW	12,2 kW	15,4 kW	21,0 kW	31 kW
Leistungsbereich (2°C)	1,7-11,6 kW	3-15 kW	4,5-17 kW	5,6 – 25,1kW	6 – 37 KW
Kältemittel R290	1,4 kg	1,4 kg	1,5 kg	2,2 kg	4,9 kg
Schallleistungspegel nach EN12102	45 dB(A)	44 dB(A)	46 dB(A)	50 dB(A)	53 dB(A)
Max. Vorlauftemperatur	70°C				
Spannung	400 V / 50 Hz				
Jahreseffizienz (35 °C)					
	ηS 240%	ηS 224 %	ηS 226%	ηS 224 %	ηS 239 %
	SCOP 6,1	SCOP 5,7	SCOP 5,73	SCOP 5,68	SCOP 6,06
Jahreseffizienz (55 °C)					
	ηS 179%	ηS 177 %	ηS 176 %	ηS 176 %	ηS 179 %
	SCOP 4,5	SCOP 4,5	SCOP 4,47	SCOP 4,48	SCOP 4,55

Typ	EU10L		EU13L		EU15L		EU20L		EU35L	
EN14511 Heizbetrieb	Leistung [kW]	COP	Leistung [kW]	COP	Leistung [kW]	COP	Leistung [kW]	COP	Leistung [kW]	COP
A7W35	3,6	6,02	5,2	5,94	6,0	5,89	10,1	5,74	12,1	6,01
A2W35	5,6	5,21	8,3	5,05	10,1	5,11	12,0	5,04	18,0	5,21
A-7W35	9,7	3,39	13,0	3,77	14,9	3,83	20,0	3,70	32,0	3,53
A-15W35	7,8	2,82	10,8	3,19	15,0	3,19	17,9	3,10	28,5	2,87
A7W45	6,5	4,76	5,2	4,57	6,3	4,47	10,6	4,56	20,5	4,67
A7W55	4,7	3,68	5,4	3,71	6,1	3,47	12,1	3,69	15,1	3,86
A-7W55	9,4	2,42	12,4	2,59	14,8	2,71	21,0	2,62	32,0	2,59